

## SAFETY DATA SHEET

### 1. IDENTIFICATION

**Product Name:** **AMAZING HASTE METHYLATED SPIRITS**

**Recommended Use:** Cleaning product, bactericide,  
raw material in other products

**Supplier:** TMK Packers Ltd  
**Address:** 2/20 Trugood Drive, East Tamaki.  
PO Box 258 031, Botany, Manukau 2163  
**Telephone:** (+64) 9 273 3753  
**Facsimile:** (+64) 9 273 3752  
**Website:** [www.tmkpackers.co.nz](http://www.tmkpackers.co.nz)



**Emergency phone:** **National Poisons Centre**  
**0800 POISON [ 0800 764 766]**

### 2. HAZARDS IDENTIFICATION

Product is classified as hazardous according to Schedules 1 to 6 of the *Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001* of the HSNO Act, 1996.

**HSNO Classifications:** 3.1B, 6.4A, 9.1D



**Signal word:** **DANGER**

**Hazard Statements:**

H225 Highly flammable liquid and vapour.  
H320 Causes eye irritation.  
H402 Harmful to aquatic life.

**Prevention Statements:**

P103 Read label before use.  
P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground container and receiving equipment.  
P241 Use explosion-proof equipment.  
P242 Use non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P264 Wash hands thoroughly after handling.  
P273 Avoid release to the environment.  
P280 Wear protective clothing, gloves and eye protection.



**Response Statements:**

P101 If medical advice is needed, have product container or label at hand.

P303 + P361 + P353 IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P332 + P313 If skin irritation occurs: Get medical advice.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation occurs: Get medical advice.

P370 + P378 in case of fire: Stop leak if safe to do so.

**Storage Statements:**

P403 + P235 Store in a well-ventilated.

P405 Store locked up.

**Disposal Statement:**

P501 Dispose of product and containers in accordance with local regulations.

**3. COMPOSITION : Information on Ingredients**

Chemical Ingredient	CAS No.	Proportion (%)
Ethyl alcohol	64-17-5	>99.9
Denatonium benzoate	3734-33-6	0.00156

**4. FIRST AID MEASURES**

For advice, contact National Poisons Centre (0800 POISON; 0800 764 766) or a doctor. Have product container or label available.

**Swallowed**

If swallowed, do NOT induce vomiting. Rinse mouth. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention.

**Skin Contact**

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists, get medical attention.

**Eye Contact**

Hold eyelids apart and flush the eye continuously with running water. Continue flushing for at least 15 minutes. Remove contact lenses if present and easy to do, after the first 5 minutes and continue rinsing. Get medical attention if irritation persists.

**Inhalation**

Move the victim to fresh air immediately. Keep warm and at rest until recovered. Get medical attention if symptoms continue. Begin artificial respiration if breathing has stopped. Get immediate medical attention.

**First Aid facilities**

Provide eye baths and safety showers close to areas where splashing may occur.



### Advice to Doctor

Treat according to symptoms. Gastric lavage may be indicated if ingested. Any product aspirated during vomiting may produce lung injury.

## 5. FIRE FIGHTING MEASURES

**Flashpoint:** 14°C

**Flammable limits:** LFL : 3.3% UFL: 24.5%

### Extinguishing media:

Dry chemical or alcohol foam or CO<sub>2</sub>. Water spray or water fog for large fires only.

### Fire & Explosion hazards:

Liquid and vapours are highly flammable. Expansion or decomposition of containers may lead to violent rupture of containers.

### Firefighting Equipment:

Full protective clothing and self-contained breathing apparatus (SCBA).

### In event of fire:

- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus and protective gloves.
- Shut off product that may 'fuel' a fire if safe to do so.
- If safe, switch off electrical equipment until vapour hazard removed.
- Allow trained personnel to attend a fire in progress, providing fire-fighters with this Safety Data Sheet.
- Prevent product and extinguishing media from escaping to drains and waterways.

**Hazards from combustion products:** Smoke, carbon dioxide, carbon monoxide.

**Hazchem Code:** 3Y



## 6. ACCIDENTAL RELEASE MEASURES

### Emergency Procedures & Containment:

Refer to "Fire Fighting Measures", "First Aid Measures" and "Stability and Reactivity"

#### Minor spills

- Remove or eliminate all ignition sources.
- Clean up spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Wear personal protective equipment.
- Contain and absorb small quantities with vermiculite or other absorbent material.
- Collect residues and waste material in a labeled container suitable for flammables.
- Seal container and dispose of safely.

#### Major spills

- Clear area of personnel and move upwind.
- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Stop leak if safe to do so
- Contain spill with sand, earth or vermiculite.
- Prevent by any means available, spillage from entering drains, sewers, watercourses, or low-lying areas.
- Eliminate sources of ignition, naked lights. No smoking.
- Increase ventilation.
- Water spray or fog may be used to disperse/absorb vapour.
- Use only spark-proof tools, e.g. shovels, and explosion proof equipment, e.g. pumps.
- Collect recoverable product into labeled contains for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labeled drums for disposal.
- Wash area and prevent run off into drains.
- If contamination of drains or waterways occurs, advise Emergency Services and Local or Regional authority.





## 7. HANDLING AND STORAGE

### Precautions for safe handling:

Read label before use. This product is highly flammable. Use in well-ventilated area. Wash hands with soap and water after handling.

Do not open near open flame, sources of heat or ignition. No smoking. Keep container closed. Handle containers with care. Open slowly to control possible pressure release. Material will accumulate static discharge. Use may require grounding leads to avoid discharge (electrical spark), spark-free tools and equipment suitable for flammables. Do not use plastic buckets.

### Conditions for safe storage:

Keep out of reach of children. Store in a cool, dry place away from direct sunlight. This product will fuel a fire in progress. Check containers periodically for leaks or distortion.

**Incompatible materials:** Natural rubber, butyl rubber, EDPM, polystyrene.

## 8. EXPOSURE CONTROLS : PERSONAL PROTECTION

### Health Exposure Standards:

A Workplace Exposure Standard (WES) has been set by Worksafe New Zealand.

WES-TWA

Ethyl alcohol 1000 ppm (1880 mg/m<sup>3</sup>)

**Biological limit values:** None established

### Engineering Controls:

#### Ventilation:

Use product outdoors or in well-ventilated area. If using product in commercial or industrial situations the use of local exhaust ventilation is recommended to control emissions near the source. Provide mechanical ventilation in confined spaces. Use explosion-proof ventilation equipment.

### Personal Protective Equipment:

**Respiratory Protection:** Where concentrations in air may exceed the limits described in the Workplace Exposure Standards, it is recommended to use a half-face filter mask to protect from overexposure by inhalation. A type "A" filter material is considered suitable for this product

**Eye Protection:** Protect eyes from splashes; wear safety glasses with side shields.

### Skin/ Body Protection:

If using product in large quantities in commercial or industrial situations, wear chemical resistant gloves, e.g. PVC, nitrile rubber, also safety footwear or safety gumboots, e.g. rubber. Always wear long sleeves and long trousers or coveralls; PVC apron.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Unit of measurement	Typical value
Appearance	-	Clear purple liquid
Odour	-	Alcohol
Flash Point	°C	14
Auto-ignition temperature	°C	363
Specific gravity @ 20°C	g/ml	0.79
Vapour Pressure @ 20°C	mm Hg	Not available
Vapour Density @ 20°C	kPa	Not available
Explosive Limits in Air	%	Not available
Viscosity	cSt	Not available
Volatiles	%vol/vol	Not available
Alkalinity/acidity (as pH)	-	Not applicable
Solubility in Water	% w/w	Completely miscible

The values listed are indicative of this product's physical and chemical properties.

## 10. STABILITY AND REACTIVITY

**Chemical Stability:** Stable at room temperature and pressure.

**Conditions to avoid:** Sources of heat and ignition, open flames.

**Hazardous decomposition products:** No decomposition products except on burning. See "Fire Fighting Measures" and "Hazardous Reactions".

**Hazardous reactions:** Strong oxidizing agents, peroxides, acid chlorides, acid anhydrides, alkali metals, ammonia.

**Hazardous polymerization:** Not known to occur.

## 11. TOXICOLOGICAL INFORMATION

### Acute Effects

#### Ingestion

May be harmful if swallowed. Aspiration into the lungs by ingestion or vomiting may result in chemical pneumonitis or pulmonary oedema. Symptoms of over-exposure are nausea, vomiting and inebriation. Product contains denatonium benzoate, a bittering agent, so ingestion is unlikely.

#### Eye Contact

May be irritating to eyes causing short term discomfort if not rinsed out immediately. Will not permanently damage eye tissue.

#### Skin Contact

May be mildly irritating to skin. Prolonged or repeated exposure will increase risk of dryness and cracking of skin.

#### Inhalation

Vapour may be irritating to nose and throat. Exposure to high concentrations over an extended time will result in headaches, dizziness, drowsiness, nausea and inebriation.



### Chronic Effects

Mild central nervous system depressant. Chronic exposure (by ingestion) may lead to liver damage.

### Other Health Effects Information:

No additional information available.

### Toxicological Information:

Not available.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity:

#### Aquatic toxicity:

Product is classified as being harmful to aquatic life. Ethyl alcohol has biocidal effect at high concentrations.

#### Persistence/degradability:

No information available to indicate product is persistent or bioaccumulative.

#### Mobility:

This product is highly volatile and will rapidly dissipate.

#### Ecotoxicity Information:

Ethyl alcohol *Daphnia magna* LC<sub>50</sub> (48 hr) 9.3 mg/L

Environmental Exposure Standards: Not set.

## 13. DISPOSAL CONSIDERATIONS

### Disposal Methods:

Care should be taken to ensure compliance with national, regional and local authority regulations. Packaging may still contain vapours that are flammable. Ensure that empty packaging is allowed to dry. If not recycled, puncture and crush before disposal to landfill. Do not use container for storage of other products.

## 14. TRANSPORT INFORMATION

UN Number: 1987

Shipping name: ETHANOL SOLUTION (ethyl alcohol solution)

Class: 3

Packing group: III

Hazchem code: 3Y

### Dangerous Goods Segregation

This product is classified as Dangerous Goods Class 3, packing group III.

Please consult NZS 5433:2012 Transport of Dangerous Goods on Land for information.



## 15. REGULATORY INFORMATION

**Country/ Region:** New Zealand  
**Inventory:** NZIoC  
**Status:** Components listed

**EPA New Zealand Approval Code:**

Denatured Alcohol Group Standard 2006; HSR002553  
Refer [www.epa.govt.nz](http://www.epa.govt.nz) for information on Controls.

## 16. OTHER INFORMATION

**Issue:** 5  
**Date of Issue:** 23<sup>rd</sup> April 2015  
**Reasons for Issue:** 5-yearly review.  
**Replaces:** 28<sup>th</sup> March 2019

**Abbreviations:**

CAS No Chemical Abstracts Number  
EPA Environmental Protection Authority  
HSNO Hazardous Substances and New Organisms  
NZIoC New Zealand Inventory of Chemicals  
STEL Short Term Exposure Limit  
TWA Time Weighted Average  
WES Workplace Exposure Standard

**References:**

Supplier Safety Data Sheet  
EPA website: [www.epa.govt.nz](http://www.epa.govt.nz)

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact TMK Packers Ltd.

END OF SAFETY DATA SHEET

